



3M™ Scott™ Vision C5 Facepiece with Radio Direct Interface



Question

How is the Vision C5 facepiece with radio direct interface different from other fireground communication systems?

Answer

Utilizing proprietary noise suppression algorithms, a mask communications unit (MCU) transmits the SCBA user's voice directly into the field radio audio path to deliver clear, intelligible outgoing radio communications.

Incoming field radio voice communications are routed to an integrated bone conduction headphone to enhance the user's hearing and understanding of incoming two-way radio communications.

Question

How does the integrated bone conduction headphone work?

Answer

System transducers send mini vibrations through the skull bone and deliver sound directly to the inner ear, bypassing the eardrum.

Question

How does the Vision C5 facepiece with radio direct interface operate with a field radio?

Answer

The Vision C5 facepiece with radio direct interface utilizes a MCU equipped with a Bluetooth® radio to provide direct wireless communications with compatible Bluetooth wireless technology enabled field radios and matching remote speaker microphones. Push-to-talk (PTT) operation of the MCU microphone is controlled by the field radio or remote speaker microphone PTT button, providing users with a familiar, easy-to-use operation interface. Incoming field radio voice communication audio can be routed to the integrated bone conduction headphone, field radio system speakers, or remote speaker to address the specific needs of the user.

Question

Which handheld field radios and remote speaker microphones can be used with the Vision C5 facepiece with radio direct interface?

Answer

The Vision C5 facepiece with radio direct interface is compatible for use with the Motorola APX series handheld field radios and matching APX series remote speaker microphones. APX radio firmware version 15.00.00 or newer is required for full system operation and is available from your Motorola Authorized APX Service Technician. Support for additional handheld field radios and matching remote speaker microphones will be announced when available.

Question

Are there specific Motorola APX radio configuration settings required for operating the APX radio and APX remote speaker microphone with the Vision C5 facepiece with radio direct interface?

Answer

Yes, specific APX radio code plug configuration settings are recommended for optimizing the operation and performance of the APX radio and APX remote speaker microphone, when used with the Vision C5 facepiece with radio direct interface. Please refer to the Motorola configuration instructions for the Vision C5 facepiece with radio direct interface. These settings will need to be configured by a Motorola Authorized APX Service Technician.

Question

How do I pair a handheld field radio with the Vision C5 facepiece with radio direct interface?

Answer

An initial Bluetooth pairing procedure is used to establish and maintain the wireless communications link between the facepiece and radio. The initial Bluetooth pairing process is intuitive and can be completed in 20 seconds or less. Please refer to the Vision C5 facepiece with radio direct interface user instructions for the initial pairing procedure.

Question

Is it necessary to pair the Vision C5 facepiece with radio direct interface and handheld field radio prior to each use?

Answer

No. After initial pairing, the facepiece ID is stored in the handheld field radio, enabling automatic re-pairing when the facepiece and field radio are both powered on.

Question

How do you power on the Vision C5 facepiece with radio direct interface?

Answer

The Vision C5 facepiece with radio direct interface incorporates a single button, providing a simple, intuitive operation for powering on/off electronics.

Question

Does the Vision C5 facepiece with radio direct interface require the user to be on air to use the radio direct interface communications system?

Answer

No. The Vision C5 facepiece with radio direct interface provides active communications when transitioning between tactical (on air) and non-tactical (off air) operations.

Question

Is the Vision C5 facepiece with radio direct interface equipped with an automatic power-off feature?

Answer

Yes. The Vision C5 facepiece with radio direct interface utilizes proprietary breath detect algorithms to detect when a user is breathing through a regulator. The facepiece will automatically power off when the system does not detect breathing for a preset time. The preset time is configurable by the end-user using the mobile application. The default setting is 20 minutes.

Question

Does the Vision C5 facepiece with radio direct interface provide voice prompts when configured with the bone conduction headphone?

Answer

Yes. The Vision C5 facepiece with radio direct interface provides verbal notification of changing system conditions when configured with the bone conduction headphone. Automated voice prompts include system power status, battery level, and Bluetooth connection status.

Question

Is there a volume adjustment for incoming radio communications?

Answer

Yes. When configured with the bone conduction headphone, the Vision C5 facepiece with radio direct interface includes a volume control switch that allows adjustments based on hearing acuity and environmental conditions.

Question

What type of battery is used with the Vision C5 facepiece with radio direct interface?

Answer

The Vision C5 facepiece with radio direct interface is powered by an intrinsically safe, rechargeable lithium-ion battery.



Personal Safety Division
3M Scott Fire & Safety
Monroe Center, P.O. Box 569
Monroe, NC 28110

Email: US-3M-ScottMonroeCSR@mmm.com
Web: 3M.com
3M.ca/ScottSafety

Question

What is the battery run-time for the Vision C5 facepiece with radio direct interface?

Answer

A fully charged battery is designed to deliver up to 15 hours of continuous run-time.

Question

Does the Vision C5 facepiece with radio direct interface come with a spare battery?

Answer

No. A single, rechargeable lithium-ion battery is included with the Vision C5 facepiece with radio direct interface. An optional spare battery is available at the time of purchase.

Question

How do I charge the battery on the Vision C5 facepiece with radio direct interface?

Answer

A 2-bay charger is available and may be used in a vehicle mount or desktop configuration and will charge two batteries simultaneously.

Question

Can I connect multiple chargers together?

Answer

Yes. Multiple chargers may be connected (i.e. daisy-chain) to expand charging capabilities, while providing a simplified installation. The charger may be installed using a hard-wired connection to the vehicle or an AC/DC adapter.

Question

Is the Vision C5 facepiece with radio direct interface configurable using a mobile application?

Answer

Yes. An iOS or Android™ compatible mobile application is available for modifying settings by the user. The mobile application is available through the [3M Software Download Portal](#) and will require authorization by an administrator before it can be used.

Question

Is the Vision C5 facepiece with radio direct interface built and tested to withstand the rigors of firefighting environments and use?

Answer

Yes. The Vision C5 facepiece with radio direct interface is a purpose-built solution designed to meet the rigorous demands and environmental conditions commonly found on the fireground. All devices are tested and certified to meet the NFPA 1981, 2018 edition standard for voice intelligibility, heat and flame resistance, water and dust ingress protection, impact resistance, vibration resistance, and intrinsic safety.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG. Android is a trademark of Google LLC.

H/S 7716A__EN 01/21 ISO 9001 Registered. Please recycle. Printed in USA © 2021, 3M. All rights reserved. 3M and Scott are trademarks of 3M. All other trademarks are the property of their respective owner. Used under license in Canada.